- Very compact design can be installed under a window sill, only 600 mm in height with a depth of only 200mm, the unit can be installed along the wall ensuring space saving
- Removable split front panel with immediate access to the main components
- Ideal for office and other commercial buildings with large fluctuation in load, the unit fits perfectly specialist applications such as libraries and hospitals

VRF Indoor Unit Concealed Chassis

INDOOR UNIT	MML-	AP0074BH-E	AP0094BH-E	AP0124BH-E	AP0154BH-E	AP0184BH-E	AP0244BH-E
CAPACITY CODE	HP	0.8	1.0	1.25	1.7	2.0	2.5
Cooling Capacity	(kW)	2.2	2.8	3.6	4.5	5.6	7.1
Heating Capacity	(kW)	2.5	3.2	4.0	5.0	6.3	8.0
UK Total Cooling / Sensible Cooling Capacity	(kW)	2.0 / 1.3	2.5 / 1.5	3.3 / 2.1	4.1 / 2.7	5.1 / 3.3	6.4 / 4.2
UK Heating Capacity	(kW)	1.7	2.2	2.7	3.4	4.3	5.4
Power Consumption	(kW)	0.056			0.090		0.095
Running Current	(Amps)	0.25			0.45		0.46
Starting Current	(Amps)	0.60			0.80		1.00
Motor Output	(Watts)	19			70		
Standard Air Flow H/M/L	(l/s)	133 / 117 / 83			200 / 167 / 133		267 / 217 / 183
Standard Air Flow H/M/L	(m3/min)	8.0 / 7.0 / 5.0			12.0 / 10.0 / 8.0		16.0 / 13.0 / 11.0
Standard Air Flow H/M/L	(m3/h)	460 / 400 / 300			740 / 600 / 490		950 / 790 / 640
External Static Pressure		0					
Sound Pressure Level H/M/L	(dBA)	36 / 34 / 32					42 / 37 / 33
Sound Power Level H/M/L	(dBA)	51 / 49 / 47					57 / 52 / 48
Main Unit Height / Width / Depth	(mm)	600 / 745 / 220			600 / 1045 / 220		
Main Unit Total Weight	(kg)	21			29		
Gas Side	(mm / “)	9.5 - 3/8			12.7 - 1/2		15.9 - 5/8
Liquid Side	(mm / “)	6.4 - 1/4			6.4 - 1/4		9.5 - 3/8
Drain Port	(mm)	20 male screw					
Power Supply		1 phase 230v 50Hz					
Suggested Fused Spur Supply	(Amps)	5					

ACCESSORIES

RBC-AMT32E	Remote Controller	Full control including service functions
RBC-AMS41E	Remote Controller Built In Timer	Full control including service functions with fully programmable 7 day timer
RBC-AMS51E-ES	Lite-Vision Plus Remote Controller	Includes timer and backlight display as well as power save functions, multilingual
RBC-AS41E	Simplified Controller	Ideal for hotel and base use applications (no service function available)
RBC-SMCN61	ON/OFF And Locking Lead	Lead to remotely switch a unit ON/OFF and to lock this function
RBC-SMTI	CN02 Connector Timer Interface Lead	Lead to provide ON/OFF control from the RBC-AMT32E remote or any central controller