

Combination guide

4-1. AJ040TXJ2KG/EU

Cooling

| Outdoor Unit | A | B | Cooling Capacity | | Capacity | | | Power Consumption | | | Current | | | Effic. NOM. Cooling at 35 °C/27 °C EER | Seasonal Efficiency (According to EN14825) Class | SEER | Qce kWh |
|-----------------------|---|----|------------------|-------|----------|-------|-------|-------------------|-----|-------|---------|-----|-----|---|---|------|------------|
| | | | W | | W | | | W | | | A | | | | | | |
| | | | A | B | MIN | STD | MAX | MIN | STD | MAX | MIN | STD | MAX | | | | |
| AJ040TXJ2KG 2 Unit | 7 | 7 | 2,000 | 2,000 | 1,300 | 4,000 | 4,700 | 300 | 900 | 1,250 | 1.7 | 4.1 | 5.7 | 4.44 | A+++ | 8.54 | 164 |
| | 7 | 9 | 1,780 | 2,220 | 1,300 | 4,000 | 4,700 | 350 | 920 | 1,270 | 1.9 | 4.2 | 5.8 | 4.35 | A+++ | 8.51 | 165 |
| | 7 | 12 | 1,450 | 2,550 | 1,300 | 4,000 | 4,700 | 350 | 930 | 1,280 | 1.9 | 4.3 | 5.9 | 4.30 | A+++ | 8.51 | 165 |
| | 9 | 9 | 2,000 | 2,000 | 1,300 | 4,000 | 4,700 | 350 | 940 | 1,290 | 1.9 | 4.3 | 5.9 | 4.26 | A+++ | 8.51 | 165 |
| | 9 | 12 | 1,670 | 2,330 | 1,300 | 4,000 | 4,700 | 350 | 950 | 1,300 | 1.9 | 4.3 | 5.9 | 4.21 | A+++ | 8.51 | 165 |

Heating

| Outdoor Unit | A | B | Heating Capacity | | Capacity | | | Power Consumption | | | Current | | | Effic. NOM. Heating at 7 °C/20 °C COP ¹ | Seasonal Efficiency (According to EN14825) Class | SCOP | P design kW | Qhe kWh |
|-----------------------|---|----|------------------|-------|----------|-------|-------|-------------------|-----|-------|---------|-----|-----|---|---|------|----------------|------------|
| | | | W | | W | | | W | | | A | | | | | | | |
| | | | A | B | MIN | STD | MAX | MIN | STD | MAX | MIN | STD | MAX | | | | | |
| AJ040TXJ2KG 2 Unit | 7 | 7 | 2,100 | 2,100 | 1,000 | 4,200 | 4,700 | 280 | 900 | 1,180 | 1.4 | 4.1 | 5.4 | 4.67 | A++ | 4.64 | 3.05 | 922 |
| | 7 | 9 | 1,840 | 2,360 | 1,000 | 4,200 | 4,700 | 280 | 920 | 1,190 | 1.4 | 4.2 | 5.4 | 4.57 | A++ | 4.61 | 3.05 | 927 |
| | 7 | 12 | 1,550 | 2,650 | 1,000 | 4,200 | 4,700 | 280 | 930 | 1,200 | 1.4 | 4.3 | 5.5 | 4.52 | A++ | 4.61 | 3.05 | 927 |
| | 9 | 9 | 2,100 | 2,100 | 1,000 | 4,200 | 4,700 | 280 | 940 | 1,210 | 1.4 | 4.3 | 5.5 | 4.47 | A++ | 4.61 | 3.05 | 927 |
| | 9 | 12 | 1,800 | 2,400 | 1,000 | 4,200 | 4,700 | 280 | 950 | 1,220 | 1.4 | 4.3 | 5.6 | 4.42 | A++ | 4.61 | 3.05 | 927 |

- EER and COP declared only for the purpose of tax deductions in force at the time of the creation of this catalogue.
- The above is the value for connecting with the following indoor units. Wind-Free™ Elite: AR07TXCAAWK, AR09TXCAAWK, AR12TXCAAWK.
- You cannot connect a single unit.
- Power consumption includes indoor unit power.

4-2. AJ050TXJ2KG/EU

Cooling

| Outdoor Unit | A | B | Cooling Capacity | | Capacity | | | Power Consumption | | | Current | | | Effic. NOM. Cooling at 35 °C/27 °C EER | Seasonal Efficiency (According to EN14825) Class | SEER | Qce kWh |
|-----------------------|----|----|------------------|-------|----------|-------|-------|-------------------|-------|-------|---------|-----|-----|---|---|------|------------|
| | | | W | | W | | | W | | | A | | | | | | |
| | | | A | B | MIN | STD | MAX | MIN | STD | MAX | MIN | STD | MAX | | | | |
| AJ050TXJ2KG 2 Unit | 7 | 7 | 2,000 | 2,000 | 1,300 | 4,000 | 4,700 | 350 | 980 | 1,290 | 1.9 | 4.5 | 5.9 | 4.08 | A+++ | 8.51 | 165 |
| | 7 | 9 | 2,040 | 2,560 | 1,300 | 4,600 | 5,200 | 350 | 1,120 | 1,520 | 1.9 | 5.1 | 7.0 | 4.11 | A+++ | 8.51 | 189 |
| | 7 | 12 | 1,820 | 3,180 | 1,400 | 5,000 | 5,500 | 350 | 1,230 | 1,510 | 1.9 | 5.6 | 6.9 | 4.07 | A+++ | 8.51 | 206 |
| | 7 | 18 | 1,430 | 3,570 | 1,400 | 5,000 | 5,500 | 350 | 1,200 | 1,510 | 1.9 | 5.5 | 6.9 | 4.15 | A+++ | 8.51 | 206 |
| | 9 | 9 | 2,500 | 2,500 | 1,400 | 5,000 | 5,500 | 350 | 1,220 | 1,500 | 1.9 | 5.6 | 6.9 | 4.10 | A+++ | 8.54 | 205 |
| | 9 | 12 | 2,080 | 2,920 | 1,400 | 5,000 | 5,500 | 350 | 1,230 | 1,510 | 1.9 | 5.6 | 6.9 | 4.07 | A+++ | 8.51 | 206 |
| | 9 | 18 | 1,670 | 3,330 | 1,400 | 5,000 | 5,500 | 350 | 1,230 | 1,510 | 1.9 | 5.5 | 6.9 | 4.15 | A+++ | 8.51 | 206 |
| | 12 | 12 | 2,500 | 2,500 | 1,400 | 5,000 | 5,500 | 350 | 1,240 | 1,520 | 1.9 | 5.7 | 7.0 | 4.03 | A+++ | 8.51 | 206 |
| | 12 | 18 | 2,060 | 2,940 | 1,400 | 5,000 | 5,500 | 350 | 1,240 | 1,520 | 1.9 | 5.6 | 7.0 | 4.15 | A+++ | 8.51 | 206 |

Heating

| Outdoor Unit | A | B | Heating Capacity | | Capacity | | | Power Consumption | | | Current | | | Effic. NOM. Heating at 7 °C/20 °C COP ¹ | Seasonal Efficiency (According to EN14825) Class | SCOP | P design kW | Qhe kWh |
|-----------------------|----|----|------------------|-------|----------|-------|-------|-------------------|-------|-------|---------|-----|-----|---|---|------|----------------|------------|
| | | | W | | W | | | W | | | A | | | | | | | |
| | | | A | B | MIN | STD | MAX | MIN | STD | MAX | MIN | STD | MAX | | | | | |
| AJ040TXJ2KG 2 Unit | 7 | 7 | 2,200 | 2,200 | 1,400 | 4,400 | 4,700 | 280 | 1,010 | 1,210 | 1.4 | 4.6 | 5.5 | 4.36 | A++ | 4.61 | 3.05 | 927 |
| | 7 | 9 | 2,230 | 2,870 | 1,400 | 5,100 | 5,460 | 280 | 1,310 | 1,610 | 1.4 | 6 | 7.4 | 3.89 | A++ | 4.61 | 4.21 | 1,277 |
| | 7 | 12 | 2,060 | 3,540 | 1,400 | 5,600 | 6,300 | 280 | 1,290 | 1,710 | 1.4 | 5.9 | 7.8 | 4.34 | A++ | 4.61 | 4.21 | 1,277 |
| | 7 | 18 | 1,530 | 4,170 | 1,400 | 5,600 | 6,300 | 280 | 1,270 | 1,70 | 1.4 | 5.7 | 7.8 | 4.41 | A++ | 4.61 | 4.07 | 1,237 |
| | 9 | 9 | 2,800 | 2,800 | 1,400 | 5,600 | 6,300 | 280 | 1,280 | 1,700 | 1.4 | 5.9 | 7.8 | 4.38 | A++ | 4.64 | 4.21 | 1,270 |
| | 9 | 12 | 2,400 | 3,200 | 1,400 | 5,600 | 6,300 | 280 | 1,290 | 1,710 | 1.4 | 5.9 | 7.8 | 4.34 | A++ | 4.61 | 4.21 | 1,277 |
| | 9 | 18 | 2,020 | 3,680 | 1,400 | 5,600 | 6,300 | 280 | 1,270 | 1,70 | 1.4 | 5.7 | 7.8 | 4.41 | A++ | 4.61 | 4.07 | 1,237 |
| | 12 | 12 | 2,800 | 2,800 | 1,400 | 5,600 | 6,300 | 280 | 1,300 | 1,720 | 1.4 | 5.9 | 7.9 | 4.31 | A++ | 4.61 | 4.21 | 1,277 |
| | 12 | 18 | 2,280 | 3,420 | 1,400 | 5,600 | 6,300 | 280 | 1,280 | 1,720 | 1.4 | 5.8 | 7.9 | 4.38 | A++ | 4.61 | 4.07 | 1,237 |

- EER and COP declared only for the purpose of tax deductions in force at the time of the creation of this catalogue.
- The above is the value for connecting with the following indoor units. Wind Free™ Elite: AR07TXCAAWK, AR09TXCAAWK, AR12TXCAAWK.
- You cannot connect a single unit.
- Power consumption includes indoor unit power.

Combination guide

4-3. AJ052TXJ3KG/EU

Cooling

| Outdoor Unit | A | B | C | Cooling Capacity | | | Capacity | | | Power Consumption | | | Current | | | Effic. NOM. Cooling at 35 °C/27 °C EER | Seasonal Efficiency (According to EN14825) Class | SEER | Qce kWh | |
|--------------|--------|----|-------|------------------|-------|-------|----------|-------|-------|-------------------|-------|-------|---------|-----|------|---|---|------|------------|-----|
| | | | | W | | | W | | | W | | | A | | | | | | | |
| | | | | A | B | C | MIN | STD | MAX | MIN | STD | MAX | MIN | STD | MAX | | | | | MIN |
| AJ052TXJ3KG | 2 Unit | 7 | 7 | | 2,000 | 2,000 | | 1,100 | 4,000 | 4,800 | 320 | 1,020 | 1,630 | 2 | 4.5 | 7.5 | 3.92 | A++ | 8.08 | 173 |
| | | 7 | 9 | | 2,040 | 2,560 | | 1,100 | 4,600 | 5,520 | 320 | 1,170 | 1,850 | 2 | 5.2 | 8.5 | 3.93 | A++ | 7.73 | 208 |
| | | 7 | 12 | | 1,820 | 3,180 | | 1,100 | 5,000 | 6,290 | 320 | 1,260 | 2,000 | 2 | 5.6 | 9.2 | 3.97 | A++ | 8.15 | 215 |
| | | 7 | 18 | | 1,490 | 3,710 | | 1,200 | 5,200 | 6,600 | 320 | 1,300 | 2,040 | 2 | 5.7 | 9.3 | 4.00 | A++ | 7.85 | 232 |
| | | 9 | 9 | | 2,500 | 2,500 | | 1,100 | 5,000 | 5,800 | 320 | 1,160 | 1,980 | 2 | 5.1 | 9.1 | 4.30 | A+++ | 8.51 | 206 |
| | | 9 | 12 | | 2,080 | 2,920 | | 1,100 | 5,000 | 6,400 | 320 | 1,250 | 2,020 | 2 | 5.5 | 9.2 | 4.00 | A++ | 8.16 | 214 |
| | 9 | 18 | | 1,730 | 3,470 | | 1,200 | 5,200 | 6,800 | 320 | 1,300 | 2,070 | 2 | 5.7 | 9.5 | 4.00 | A++ | 7.85 | 232 | |
| | 12 | 12 | | 2,600 | 2,600 | | 1,100 | 5,200 | 6,560 | 320 | 1,300 | 2,040 | 2 | 5.7 | 9.3 | 4.00 | A++ | 8.16 | 214 | |
| | 3 Unit | 7 | 7 | 7 | 1,730 | 1,730 | 1,740 | 1,450 | 5,200 | 6,380 | 330 | 1,280 | 2,020 | 2 | 5.7 | 9.2 | 4.06 | A++ | 7.68 | 237 |
| | | 7 | 7 | 9 | 1,600 | 1,600 | 2,000 | 1,450 | 5,200 | 6,490 | 330 | 1,290 | 2,040 | 2 | 5.7 | 9.3 | 4.03 | A++ | 7.67 | 237 |
| | | 7 | 7 | 12 | 1,390 | 1,390 | 2,420 | 1,450 | 5,200 | 6,800 | 330 | 1,270 | 2,070 | 2 | 5.6 | 9.5 | 4.09 | A++ | 7.69 | 237 |
| | | 7 | 9 | 9 | 1,480 | 1,860 | 1,860 | 1,450 | 5,200 | 6,600 | 330 | 1,260 | 2,040 | 2 | 5.6 | 9.3 | 4.13 | A++ | 7.70 | 236 |
| 7 | | 9 | 12 | 1,300 | 1,630 | 2,270 | 1,450 | 5,200 | 6,800 | 330 | 1,270 | 2,070 | 2 | 5.6 | 9.5 | 4.11 | A++ | 7.69 | 237 | |
| 9 | | 9 | 9 | 1,730 | 1,730 | 1,740 | 1,450 | 5,200 | 6,800 | 330 | 1,250 | 2,070 | 2 | 5.5 | 9.5 | 4.16 | A++ | 7.70 | 236 | |
| 9 | 9 | 12 | 1,530 | 1,530 | 2,140 | 1,450 | 5,200 | 6,800 | 330 | 1,250 | 2,070 | 2 | 5.5 | 9.5 | 4.16 | A++ | 8.08 | 225 | | |

Heating

| Outdoor Unit | A | B | C | Heating Capacity | | | Capacity | | | Power Consumption | | | Current | | | Effic. NOM. Heating at 7 °C/20 °C EER | Seasonal Efficiency (According to EN14825) Class | SCOP | P design kWh | Qhe kWh | |
|--------------|--------|----|-------|------------------|-------|-------|----------|-------|-------|-------------------|-------|-------|---------|-----|------|--|---|------|-----------------|------------|-------|
| | | | | W | | | W | | | W | | | A | | | | | | | | |
| | | | | A | B | C | MIN | STD | MAX | MIN | STD | MAX | MIN | STD | MAX | | | | | | MIN |
| AJ052TXJ3KG | 2 Unit | 7 | 7 | | 2,200 | 2,200 | | 950 | 4,400 | 5,060 | 280 | 1,150 | 1,510 | 1.7 | 5.4 | 6.9 | 3.83 | A+ | 4.40 | 3.05 | 970 |
| | | 7 | 9 | | 2,040 | 3,060 | | 950 | 5,100 | 5,870 | 280 | 1,320 | 1,830 | 1.7 | 6.1 | 8.4 | 3.86 | A+ | 4.35 | 4.21 | 1,352 |
| | | 7 | 12 | | 1,990 | 3,610 | | 950 | 5,600 | 6,440 | 280 | 1,450 | 1,860 | 1.7 | 6.7 | 8.5 | 3.86 | A+ | 4.34 | 4.60 | 1,484 |
| | | 7 | 18 | | 1,610 | 4,390 | | 950 | 6,000 | 6,900 | 280 | 1,570 | 1,860 | 1.7 | 7.2 | 8.5 | 3.82 | A+ | 4.27 | 4.28 | 1,401 |
| | | 9 | 9 | | 2,900 | 2,900 | | 950 | 5,800 | 6,300 | 280 | 1,510 | 1,910 | 1.7 | 6.9 | 8.7 | 3.84 | A++ | 4.60 | 4.60 | 1,400 |
| | | 9 | 12 | | 2,620 | 3,180 | | 950 | 5,800 | 6,300 | 280 | 1,510 | 1,910 | 1.7 | 6.9 | 8.7 | 3.84 | A+ | 4.34 | 4.60 | 1,484 |
| | 9 | 18 | | 2,240 | 4,060 | | 950 | 6,300 | 7,300 | 280 | 1,640 | 1,830 | 1.7 | 7.5 | 8.4 | 3.84 | A+ | 4.27 | 4.28 | 1,401 | |
| | 12 | 12 | | 2,950 | 2,950 | | 950 | 5,900 | 6,880 | 280 | 1,530 | 1,860 | 1.7 | 7.0 | 8.5 | 3.86 | A+ | 4.34 | 4.60 | 1,484 | |
| | 3 Unit | 7 | 7 | 7 | 1,930 | 1,930 | 1,940 | 1,000 | 5,800 | 6,760 | 280 | 1,500 | 1,840 | 1.7 | 6.9 | 8.4 | 3.87 | A+ | 4.30 | 4.60 | 1,497 |
| | | 7 | 7 | 9 | 1,690 | 1,690 | 2,520 | 1,000 | 5,900 | 6,840 | 280 | 1,550 | 1,840 | 1.7 | 7.1 | 8.4 | 3.81 | A+ | 4.30 | 4.60 | 1,497 |
| | | 7 | 7 | 12 | 1,650 | 1,650 | 3,000 | 1,000 | 6,300 | 7,300 | 280 | 1,560 | 1,830 | 1.7 | 7.1 | 8.4 | 4.04 | A+ | 4.30 | 4.60 | 1,497 |
| | | 7 | 9 | 9 | 1,500 | 2,250 | 2,250 | 1,000 | 6,000 | 6,920 | 280 | 1,500 | 1,840 | 1.7 | 6.9 | 8.4 | 4.00 | A+ | 4.30 | 4.60 | 1,497 |
| 7 | | 9 | 12 | 1,460 | 2,190 | 2,650 | 1,000 | 6,300 | 7,300 | 280 | 1,530 | 1,830 | 1.7 | 7.0 | 8.4 | 4.12 | A+ | 4.30 | 4.60 | 1,497 | |
| 9 | | 9 | 9 | 2,100 | 2,100 | 2,100 | 1,000 | 6,300 | 7,300 | 280 | 1,320 | 1,830 | 1.7 | 6.1 | 8.4 | 4.77 | A+ | 4.30 | 4.60 | 1,497 | |
| 9 | 9 | 12 | 1,850 | 1,850 | 2,600 | 1,000 | 6,300 | 7,300 | 280 | 1,320 | 1,830 | 1.7 | 6.1 | 8.4 | 4.77 | A+ | 4.30 | 4.60 | 1,497 | | |

- EER and COP declared only for the purpose of tax deductions in force at the time of the creation of this catalogue.
- The above is the value for connecting with the following indoor units. Wind-Free™ Elite: AR07TXCAAWK, AR09TXCAAWK, AR12TXCAAWK.
- You cannot connect a single unit.
- Power consumption includes indoor unit power.

4-4. AJ068TXJ3KG/EU

Cooling

| Outdoor Unit | A | B | C | Cooling Capacity | | | Capacity | | | Power Consumption | | | Current | | | Effic. NOM. Cooling at 35 °C/27 °C EER | Seasonal Efficiency (According to EN14825) Class | SEER | Qce kWh | |
|--------------|--------|----|-------|------------------|-------|-------|----------|-------|-------|-------------------|-------|-------|---------|------|------|---|---|------|------------|-----|
| | | | | W | | | W | | | W | | | A | | | | | | | |
| | | | | A | B | C | MIN | STD | MAX | MIN | STD | MAX | MIN | STD | MAX | | | | | MIN |
| AJ068TXJ3KG | 2 Unit | 7 | 7 | | 2,000 | 2,000 | | 1,300 | 4,000 | 4,800 | 420 | 1,110 | 1,480 | 2.3 | 5.2 | 6.8 | 3.60 | A++ | 7.55 | 185 |
| | | 7 | 9 | | 2,000 | 2,500 | | 1,300 | 4,500 | 5,520 | 420 | 1,270 | 1,680 | 2.3 | 5.9 | 7.7 | 3.54 | A++ | 7.47 | 211 |
| | | 7 | 12 | | 2,000 | 3,500 | | 1,300 | 5,500 | 6,550 | 420 | 1,500 | 2,470 | 2.3 | 6.9 | 11.3 | 3.50 | A++ | 7.14 | 270 |
| | | 7 | 18 | | 1,860 | 4,640 | | 1,300 | 6,500 | 7,740 | 420 | 1,660 | 2,690 | 2.3 | 7.6 | 12.3 | 3.62 | A++ | 7.54 | 302 |
| | | 9 | 9 | | 2,500 | 2,500 | | 1,300 | 5,000 | 5,950 | 420 | 1,430 | 2,260 | 2.3 | 6.6 | 10.3 | 3.50 | A++ | 7.55 | 232 |
| | | 9 | 12 | | 2,500 | 3,500 | | 1,300 | 6,000 | 7,140 | 420 | 1,650 | 2,670 | 2.3 | 7.5 | 12.2 | 3.64 | A++ | 7.48 | 281 |
| | 9 | 18 | | 2,270 | 4,530 | | 1,380 | 6,800 | 8,090 | 430 | 1,870 | 2,660 | 2.3 | 8.5 | 12.2 | 3.64 | A++ | 7.57 | 314 | |
| | 12 | 12 | | 3,250 | 3,250 | | 1,300 | 6,500 | 7,740 | 420 | 1,770 | 2,700 | 2.3 | 8.0 | 12.4 | 3.67 | A++ | 7.56 | 301 | |
| | 12 | 18 | | 2,800 | 4,000 | | 1,380 | 6,800 | 8,090 | 430 | 1,880 | 2,670 | 2.3 | 8.5 | 12.2 | 3.62 | A++ | 7.56 | 315 | |
| | 18 | 18 | | 3,400 | 3,400 | | 1,380 | 6,800 | 8,090 | 430 | 1,850 | 2,660 | 2.3 | 8.4 | 12.2 | 3.68 | A++ | 7.58 | 314 | |
| | 3 Unit | 7 | 7 | 7 | 2,000 | 2,000 | 2,000 | 1,800 | 6,000 | 7,400 | 440 | 1,620 | 2,650 | 2.3 | 7.4 | 12.1 | 3.70 | A++ | 7.62 | 276 |
| | | 7 | 7 | 9 | 2,000 | 2,000 | 2,500 | 1,800 | 6,500 | 8,000 | 440 | 1,770 | 2,690 | 2.3 | 8.0 | 12.3 | 3.67 | A++ | 7.64 | 298 |
| | | 7 | 7 | 12 | 1,810 | 1,810 | 3,180 | 1,800 | 6,800 | 8,400 | 440 | 1,850 | 2,700 | 2.3 | 8.4 | 12.4 | 3.68 | A++ | 7.67 | 310 |
| | | 7 | 7 | 18 | 1,510 | 1,510 | 3,780 | 1,800 | 6,800 | 8,400 | 440 | 1,800 | 2,690 | 2.3 | 8.1 | 12.3 | 3.78 | A++ | 7.69 | 309 |
| | | 7 | 9 | 9 | 1,860 | 2,320 | 2,320 | 1,800 | 6,500 | 8,000 | 440 | 1,670 | 2,690 | 2.3 | 7.6 | 12.3 | 3.90 | A++ | 7.75 | 293 |
| | | 7 | 9 | 12 | 1,700 | 2,130 | 2,970 | 1,800 | 6,800 | 8,400 | 440 | 1,840 | 2,690 | 2.3 | 8.3 | 12.3 | 3.70 | A++ | 7.67 | 310 |
| | | 7 | 9 | 18 | 1,430 | 1,790 | 3,580 | 1,800 | 6,800 | 8,400 | 440 | 1,830 | 2,690 | 2.3 | 8.3 | 12.3 | 3.72 | A++ | 7.68 | 310 |
| | | 7 | 12 | 12 | 1,520 | 2,640 | 2,640 | 1,800 | 6,800 | 8,400 | 440 | 1,830 | 2,700 | 2.3 | 8.3 | 12.4 | 3.72 | A++ | 7.68 | 310 |
| 7 | | 12 | 18 | 1,300 | 2,270 | 3,230 | 1,800 | 6,800 | 8,400 | 440 | 1,830 | 2,700 | 2.3 | 8.3 | 12.4 | 3.72 | A++ | 7.68 | 310 | |
| 9 | | 9 | 9 | 2,260 | 2,270 | 2,270 | 1,800 | 6,800 | 8,400 | 440 | 1,820 | 2,690 | 2.3 | 8.3 | 12.3 | 3.74 | A++ | 7.68 | 310 | |
| 9 | | 9 | 12 | 2,000 | 2,000 | 2,800 | 1,800 | 6,800 | 8,400 | 440 | 1,820 | 2,700 | 2.3 | 8.3 | 12.4 | 3.74 | A++ | 7.68 | 310 | |
| 9 | | 9 | 18 | 1,700 | 1,700 | 3,400 | 1,800 | 6,800 | 8,400 | 440 | 1,810 | 2,690 | 2.3 | 8.2 | 12.3 | 3.76 | A++ | 7.69 | 310 | |
| 9 | 12 | 12 | 1,780 | 2,510 | 2,510 | 1,800 | 6,800 | 8,400 | 440 | 1,810 | 2,700 | 2.3 | 8.2 | 12.4 | 3.76 | A++ | 7.69 | 310 | | |
| 9 | 12 | 18 | 1,550 | 2,160 | 3,090 | 1,800 | 6,800 | 8,400 | 440 | 1,800 | 2,700 | 2.3 | 8.1 | 12.4 | 3.78 | A++ | 7.69 | 309 | | |
| 12 | 12 | 12 | 2,260 | 2,270 | 2,270 | 1,800 | 6,800 | 8,400 | 440 | 1,800 | 2,710 | 2.3 | 8.1 | 12.4 | 3.78 | A++ | 7.69 | 309 | | |

Heating

| Outdoor Unit | A | B | C | Heating Capacity | | | Capacity | | | Power Consumption | | | Current | | | Effic. NOM. Heating at 7 °C/20 °C EER | Seasonal Efficiency (According to EN14825) Class | SCOP | P design kWh | Qhe kWh |
|--------------|---|---|---|------------------|---|--|----------|--|--|-------------------|--|--|---------|--|--|--|---|------|-----------------|------------|
| | | | | W | | | W | | | W | | | A | | | | | | | |
| | | | | A | B | | | | | | | | | | | | | | | |

Combination guide

4-5. AJ080TXJ4KG/EU

Cooling

| Outdoor Unit | A | B | C | D | Cooling Capacity | | | | Capacity | | | Power Consumption | | | Current | | | Effic. NOM. Cooling at 35 °C/ 27 °C EER | Seasonal Efficiency (According to EN14825) Class | SEER | Qce kWh | |
|--------------|--------|----|----|-------|------------------|-------|-------|-------|----------|-------|-------|-------------------|-------|-------|---------|------|------|--|---|------|------------|-----|
| | | | | | W | | | | W | | | W | | | A | | | | | | | |
| | | | | | A | B | C | D | MIN | STD | MAX | MIN | STD | MAX | MIN | STD | MAX | | | | | MIN |
| AJ080TXJ4KG | 2 Unit | 7 | 7 | | | 2,000 | 2,000 | | | 1,640 | 4,000 | 4,800 | 410 | 1,110 | 1,490 | 1.9 | 4.9 | 6.8 | 3.60 | A++ | 7.55 | 185 |
| | | 7 | 9 | | | 2,040 | 2,560 | | | 1,690 | 4,600 | 5,520 | 420 | 1,310 | 1,720 | 1.9 | 5.8 | 7.9 | 3.51 | A++ | 7.47 | 216 |
| | | 7 | 12 | | | 2,000 | 3,500 | | | 1,770 | 5,500 | 6,600 | 430 | 1,570 | 2,050 | 2.0 | 6.9 | 9.4 | 3.50 | A++ | 7.14 | 270 |
| | | 7 | 18 | | | 2,060 | 5,140 | | | 1,900 | 7,200 | 8,640 | 580 | 2,050 | 2,690 | 2.7 | 8.9 | 12.3 | 3.51 | A++ | 7.31 | 345 |
| | | 7 | 24 | | | 1,690 | 5,760 | | | 1,900 | 7,450 | 8,640 | 580 | 2,130 | 2,730 | 2.7 | 9.3 | 12.5 | 3.50 | A++ | 7.25 | 359 |
| | | 9 | 9 | | | 2,600 | 2,600 | | | 1,750 | 5,200 | 6,240 | 420 | 1,480 | 2,000 | 1.9 | 6.5 | 9.2 | 3.51 | A++ | 7.3 | 249 |
| | 9 | 12 | | | 2,540 | 3,560 | | | 1,820 | 6,100 | 7,320 | 440 | 1,680 | 2,260 | 2.0 | 7.4 | 10.3 | 3.63 | A++ | 7.46 | 286 | |
| | 9 | 18 | | | 2,400 | 4,800 | | | 1,900 | 7,200 | 8,640 | 580 | 2,050 | 2,690 | 2.7 | 8.9 | 12.3 | 3.51 | A++ | 7.31 | 345 | |
| | 9 | 24 | | | 2,030 | 5,520 | | | 1,900 | 7,550 | 8,760 | 580 | 2,150 | 2,760 | 2.7 | 9.4 | 12.6 | 3.51 | A++ | 7.26 | 364 | |
| | 12 | 12 | | | 3,500 | 3,500 | | | 1,900 | 7,000 | 8,000 | 580 | 2,000 | 2,620 | 2.7 | 8.7 | 12.0 | 3.50 | A++ | 7.3 | 336 | |
| | 12 | 18 | | | 3,030 | 4,320 | | | 1,900 | 7,350 | 8,820 | 580 | 2,110 | 2,750 | 2.7 | 9.2 | 12.6 | 3.48 | A++ | 7.27 | 354 | |
| | 12 | 24 | | | 2,620 | 5,080 | | | 1,900 | 7,700 | 8,930 | 580 | 2,180 | 2,780 | 2.7 | 9.5 | 12.7 | 3.53 | A++ | 7.21 | 377 | |
| | 18 | 18 | | | 3,830 | 3,830 | | | 1,900 | 7,660 | 9,180 | 580 | 2,120 | 2,860 | 2.7 | 9.2 | 13.1 | 3.61 | A++ | 7.21 | 372 | |
| | 18 | 24 | | | 3,310 | 4,490 | | | 1,900 | 7,800 | 8,970 | 580 | 2,150 | 2,820 | 2.7 | 9.4 | 12.9 | 3.63 | A++ | 7.22 | 378 | |
| | 3 Unit | 7 | 7 | 7 | | 2,000 | 2,000 | 2,000 | | 1,810 | 6,000 | 7,200 | 440 | 1,620 | 2,310 | 2.0 | 6.9 | 10.6 | 3.70 | A++ | 7.62 | 276 |
| | | 7 | 7 | 9 | | 2,030 | 2,030 | 2,540 | | 1,870 | 6,600 | 7,920 | 440 | 1,810 | 2,500 | 2.0 | 7.7 | 11.4 | 3.65 | A++ | 7.58 | 305 |
| | | 7 | 7 | 12 | | 1,920 | 1,920 | 3,360 | | 1,900 | 7,200 | 9,000 | 580 | 2,020 | 2,780 | 2.7 | 8.6 | 12.7 | 3.56 | A++ | 7.45 | 338 |
| | | 7 | 7 | 18 | | 1,680 | 1,680 | 4,190 | | 1,900 | 7,550 | 9,180 | 580 | 2,130 | 2,730 | 2.7 | 9.1 | 12.5 | 3.54 | A++ | 7.75 | 341 |
| 7 | | 7 | 24 | | 1,480 | 1,480 | 5,040 | | 1,900 | 8,000 | 9,300 | 580 | 2,090 | 2,870 | 2.7 | 8.9 | 13.1 | 3.83 | A++ | 7.75 | 361 | |
| 7 | | 9 | 9 | | 2,000 | 2,500 | 2,500 | | 1,900 | 7,000 | 8,640 | 580 | 1,930 | 2,680 | 2.7 | 8.2 | 12.3 | 3.63 | A++ | 7.35 | 348 | |
| 7 | | 9 | 12 | | 1,830 | 2,280 | 3,200 | | 1,900 | 7,310 | 9,060 | 580 | 2,030 | 2,690 | 2.7 | 8.6 | 12.3 | 3.60 | A++ | 7.75 | 330 | |
| 7 | | 9 | 18 | | 1,610 | 2,010 | 4,030 | | 1,900 | 7,650 | 9,250 | 580 | 2,050 | 2,730 | 2.7 | 8.7 | 12.5 | 3.73 | A++ | 7.81 | 343 | |
| 7 | | 9 | 24 | | 1,420 | 1,770 | 4,810 | | 1,900 | 8,000 | 9,300 | 580 | 2,030 | 2,870 | 2.7 | 8.7 | 13.1 | 3.94 | A++ | 7.77 | 360 | |
| 7 | | 12 | 12 | | 1,680 | 2,930 | 2,930 | | 1,900 | 7,540 | 9,160 | 580 | 2,070 | 2,730 | 2.7 | 8.8 | 12.5 | 3.64 | A++ | 7.78 | 339 | |
| 7 | | 12 | 18 | | 1,500 | 2,630 | 3,750 | | 1,900 | 7,880 | 9,300 | 580 | 2,050 | 2,820 | 2.7 | 8.7 | 12.9 | 3.84 | A++ | 7.74 | 356 | |
| 7 | | 18 | 18 | | 1,330 | 3,330 | 3,330 | | 1,900 | 8,000 | 9,300 | 580 | 2,010 | 2,910 | 2.7 | 8.6 | 13.3 | 3.98 | A++ | 7.78 | 360 | |
| 9 | | 9 | 9 | | 2,400 | 2,400 | 2,400 | | 1,900 | 7,200 | 9,030 | 580 | 1,950 | 2,640 | 2.7 | 8.3 | 12.1 | 3.69 | A++ | 7.77 | 324 | |
| 9 | | 9 | 12 | | 2,180 | 2,180 | 3,060 | | 1,900 | 7,420 | 9,130 | 580 | 2,040 | 2,690 | 2.7 | 8.7 | 12.3 | 3.64 | A++ | 7.77 | 334 | |
| 9 | | 9 | 18 | | 1,940 | 1,940 | 3,890 | | 1,900 | 7,770 | 9,300 | 580 | 1,950 | 2,780 | 2.7 | 8.3 | 12.7 | 3.98 | A++ | 7.77 | 350 | |
| 9 | | 9 | 24 | | 1,690 | 1,690 | 4,610 | | 1,900 | 8,000 | 9,300 | 580 | 2,000 | 2,910 | 2.7 | 8.5 | 13.3 | 4.00 | A++ | 7.79 | 359 | |
| 9 | | 12 | 12 | | 2,010 | 2,820 | 2,820 | | 1,900 | 7,650 | 9,230 | 580 | 2,080 | 2,730 | 2.7 | 8.9 | 12.5 | 3.68 | A++ | 7.79 | 344 | |
| 9 | | 12 | 18 | | 1,820 | 2,550 | 3,640 | | 1,900 | 8,000 | 9,300 | 580 | 2,020 | 2,870 | 2.7 | 8.6 | 13.1 | 3.96 | A++ | 7.78 | 360 | |
| 12 | 12 | 12 | | 2,630 | 2,630 | 2,630 | | 1,900 | 7,890 | 9,300 | 580 | 2,120 | 2,820 | 2.7 | 9.0 | 12.9 | 3.72 | A++ | 7.71 | 358 | | |
| 12 | 12 | 18 | | 2,330 | 2,330 | 3,330 | | 1,900 | 8,000 | 9,300 | 580 | 2,110 | 2,910 | 2.7 | 9.0 | 13.3 | 3.79 | A++ | 7.74 | 362 | | |
| 4 Unit | 7 | 7 | 7 | 7 | 1,830 | 1,830 | 1,830 | 1,830 | 1,900 | 7,320 | 9,050 | 580 | 1,800 | 2,690 | 2.7 | 8.2 | 12.3 | 4.06 | A++ | 7.67 | 334 | |
| | 7 | 7 | 7 | 9 | 1,750 | 1,750 | 1,750 | 2,190 | 1,900 | 7,440 | 9,120 | 580 | 1,850 | 2,690 | 2.7 | 8.4 | 12.3 | 4.02 | A++ | 7.67 | 340 | |
| | 7 | 7 | 7 | 12 | 1,610 | 1,610 | 1,610 | 2,820 | 1,900 | 7,650 | 9,220 | 580 | 1,900 | 2,730 | 2.7 | 8.6 | 12.5 | 4.03 | A++ | 7.69 | 348 | |
| | 7 | 7 | 7 | 18 | 1,450 | 1,450 | 1,450 | 3,650 | 1,900 | 8,000 | 9,300 | 580 | 2,000 | 2,870 | 2.7 | 9.0 | 13.1 | 4.00 | A++ | 7.7 | 364 | |
| | 7 | 7 | 9 | 9 | 1,680 | 1,680 | 2,090 | 2,090 | 1,900 | 7,540 | 9,180 | 580 | 1,870 | 2,730 | 2.7 | 8.5 | 12.5 | 4.03 | A++ | 7.68 | 344 | |
| | 7 | 7 | 9 | 12 | 1,550 | 1,550 | 1,940 | 2,720 | 1,900 | 7,760 | 9,280 | 580 | 1,940 | 2,780 | 2.7 | 8.8 | 12.7 | 4.00 | A++ | 7.69 | 353 | |
| | 7 | 7 | 9 | 18 | 1,390 | 1,390 | 1,740 | 3,480 | 1,900 | 8,000 | 9,300 | 580 | 1,970 | 2,870 | 2.7 | 8.9 | 13.1 | 4.06 | A++ | 7.72 | 363 | |
| | 7 | 7 | 12 | 12 | 1,450 | 1,450 | 2,550 | 2,550 | 1,900 | 8,000 | 9,300 | 580 | 1,990 | 2,870 | 2.7 | 9.0 | 13.1 | 4.02 | A++ | 7.71 | 363 | |
| | 7 | 9 | 9 | 9 | 1,610 | 2,010 | 2,010 | 2,010 | 1,900 | 7,650 | 9,250 | 580 | 1,900 | 2,730 | 2.7 | 8.6 | 12.5 | 4.03 | A++ | 7.69 | 348 | |
| | 7 | 9 | 9 | 12 | 1,500 | 1,880 | 1,880 | 2,630 | 1,900 | 7,890 | 9,300 | 580 | 1,960 | 2,820 | 2.7 | 8.9 | 12.9 | 4.03 | A++ | 7.7 | 359 | |
| | 7 | 9 | 9 | 18 | 1,330 | 1,670 | 1,670 | 3,330 | 1,900 | 8,000 | 9,300 | 580 | 1,970 | 2,910 | 2.7 | 8.9 | 13.3 | 4.06 | A++ | 7.72 | 363 | |
| | 7 | 9 | 12 | 12 | 1,400 | 1,740 | 2,430 | 2,430 | 1,900 | 8,000 | 9,300 | 580 | 1,970 | 2,870 | 2.7 | 8.9 | 13.1 | 4.06 | A++ | 7.72 | 363 | |
| | 9 | 9 | 9 | 9 | 1,940 | 1,940 | 1,940 | 1,940 | 1,900 | 7,760 | 9,300 | 580 | 1,940 | 2,780 | 2.7 | 8.8 | 12.7 | 4.00 | A++ | 7.69 | 353 | |
| | 9 | 9 | 9 | 12 | 1,820 | 1,820 | 1,820 | 2,540 | 1,900 | 8,000 | 9,300 | 580 | 1,970 | 2,870 | 2.7 | 8.9 | 13.1 | 4.06 | A++ | 7.72 | 363 | |
| | 9 | 9 | 12 | 12 | 1,670 | 1,670 | 2,330 | 2,330 | 1,900 | 8,000 | 9,300 | 580 | 1,970 | 2,910 | 2.7 | 8.9 | 13.3 | 4.06 | A++ | 7.72 | 363 | |

Heating

| Outdoor Unit | A | B | C | D | Heating Capacity | | | | Capacity | | | Power Consumption | | | Current | | | Effic. NOM. Heating at 7 °C/20 °C COP ¹ | Seasonal Efficiency (According to EN14825) Class | SCOP | p design kW | Qhe kWh | |
|--------------|--------|----|----|---|------------------|-------|-------|---|----------|-------|-------|-------------------|-------|-------|---------|-----|------|---|---|------|----------------|------------|-------|
| | | | | | W | | | | W | | | W | | | A | | | | | | | | |
| | | | | | A | B | C | D | MIN | STD | MAX | MIN | STD | MAX | MIN | STD | MAX | | | | | | MIN |
| AJ080TXJ4KG | 2 Unit | 7 | 7 | | | 2,200 | 2,200 | | | 1,980 | 4,400 | 5,060 | 600 | 1,150 | 1,530 | 2.7 | 4.9 | 7.0 | 3.83 | A+ | 4.25 | 3.05 | 1,006 |
| | | 7 | 9 | | | 2,040 | 3,060 | | | 2,040 | 5,100 | 5,870 | 610 | 1,290 | 1,700 | 2.8 | 5.5 | 7.8 | 3.95 | A+ | 4.20 | 4.21 | 1,401 |
| | | 7 | 12 | | | 2,130 | 3,870 | | | 2,110 | 6,000 | 6,900 | 610 | 1,530 | 2,110 | 2.8 | 6.5 | 9.7 | 3.92 | A+ | 4.11 | 4.91 | 1,669 |
| | | 7 | 18 | | | 2,090 | 5,710 | | | 2,200 | 7,800 | 9,130 | 620 | 1,920 | 2,580 | 2.8 | 8.2 | 11.8 | 4.06 | A+ | 4.18 | 5.09 | 1,705 |
| | | 7 | 24 | | | 1,790 | 6,330 | | | 2,200 | 8,120 | 9,300 | 620 | 2,000 | 2,600 | 2.8 | 8.5 | 11.9 | 4.06 | A+ | 4.18 | 5.2 | 1,742 |
| | | 9 | 9 | | | 2,900 | 2,900 | | | 2,100 | 5,800 | 6,670 | 610 | 1,470 | 1,930 | 2.8 | 6.3 | 8.8 | 3.94 | A+ | 4.11 | 4.91 | 1,669 |
| | 9 | 12 | | | 3,030 | 3,670 | | | 2,170 | 6,700 | 7,710 | 610 | 1,730 | 2,330 | 2.8 | 7.4 | 10.7 | 3.87 | A+ | 4.11 | 4.91 | 1,669 | |
| | 9 | 18 | | | 2,770 | 5,030 | | | 2,200 | 7,800 | 9,360 | | | | | | | | | | | | |

Combination guide

4-6. AJ100TXJ5KG/EU

Cooling

| Outdoor Unit | A | B | C | D | E | Cooling Capacity | | | | | Capacity | | | Power Consumption | | | Current | | | Effic. NOM. Cooling at 35°C/27°C EER | Seasonal Efficiency (According to EN14825) Class | SEER | Qce kWh | |
|--------------|--------|----|----|----|-------|------------------|-------|-------|-------|-------|----------|--------|--------|-------------------|-------|-------|---------|------|------|---|---|------|------------|-----|
| | | | | | | W | | | | | W | | | W | | | A | | | | | | | |
| | | | | | | A | B | C | D | E | MIN | STD | MAX | MIN | STD | MAX | MIN | STD | MAX | | | | | MIN |
| AJ100TXJ5KG | 2 Unit | 7 | 7 | | | | 2,000 | 2,000 | | | | 1,680 | 4,000 | 4,900 | 610 | 1,110 | 1,650 | 2.8 | 4.7 | 7.6 | 3.60 | A++ | 7.28 | 192 |
| | | 7 | 9 | | | | 2,000 | 2,500 | | | | 1,680 | 4,500 | 5,530 | 610 | 1,270 | 1,860 | 2.8 | 5.4 | 8.5 | 3.55 | A++ | 7.39 | 213 |
| | | 7 | 12 | | | | 2,000 | 3,500 | | | | 1,710 | 5,500 | 6,950 | 620 | 1,570 | 2,330 | 2.8 | 6.7 | 10.7 | 3.50 | A++ | 7.40 | 260 |
| | | 7 | 18 | | | | 2,000 | 5,000 | | | | 2,210 | 7,000 | 8,690 | 630 | 1,970 | 2,910 | 2.9 | 8.4 | 13.3 | 3.55 | A++ | 7.37 | 332 |
| | | 7 | 24 | | | | 1,830 | 6,240 | | | | 2,280 | 8,070 | 10,110 | 650 | 2,290 | 3,390 | 3.0 | 9.8 | 15.5 | 3.52 | A++ | 7.30 | 387 |
| | | 9 | 9 | | | | 2,500 | 2,500 | | | | 1,680 | 5,000 | 6,320 | 610 | 1,400 | 2,120 | 2.8 | 6.0 | 9.7 | 3.58 | A++ | 7.49 | 234 |
| | | 9 | 12 | | | | 2,500 | 3,500 | | | | 1,710 | 6,000 | 7,270 | 620 | 1,690 | 2,430 | 2.8 | 7.2 | 11.1 | 3.55 | A++ | 7.46 | 282 |
| | | 9 | 18 | | | | 2,500 | 5,000 | | | | 2,210 | 7,500 | 9,320 | 630 | 2,140 | 3,120 | 2.9 | 9.1 | 14.3 | 3.51 | A++ | 7.33 | 358 |
| | | 9 | 24 | | | | 2,190 | 5,960 | | | | 2,280 | 8,150 | 10,110 | 650 | 2,340 | 3,390 | 3.0 | 10.0 | 15.5 | 3.48 | A++ | 7.30 | 391 |
| | | 12 | 12 | | | | 3,500 | 3,500 | | | | 2,170 | 7,000 | 8,530 | 620 | 1,960 | 2,850 | 2.8 | 8.4 | 13.0 | 3.58 | A++ | 7.38 | 332 |
| | 12 | 18 | | | | 3,300 | 4,720 | | | | 2,240 | 8,020 | 9,950 | 640 | 2,260 | 3,330 | 2.9 | 9.6 | 15.2 | 3.55 | A++ | 7.31 | 386 | |
| | 12 | 24 | | | | 2,920 | 5,670 | | | | 2,480 | 8,590 | 10,740 | 660 | 2,480 | 3,600 | 3.0 | 10.6 | 16.5 | 3.47 | A++ | 7.15 | 420 | |
| | 18 | 18 | | | | 4,280 | 4,280 | | | | 2,440 | 8,560 | 10,430 | 650 | 2,460 | 3,500 | 3.0 | 10.5 | 16.0 | 3.48 | A++ | 7.15 | 419 | |
| | 18 | 24 | | | | 3,740 | 5,080 | | | | 2,510 | 8,820 | 10,900 | 670 | 2,470 | 3,670 | 3.1 | 10.5 | 16.8 | 3.57 | A++ | 7.29 | 423 | |
| | 24 | 24 | | | | 4,550 | 4,550 | | | | 3,110 | 9,100 | 11,000 | 690 | 2,560 | 3,740 | 3.2 | 10.9 | 17.1 | 3.55 | A++ | 7.30 | 436 | |
| | 3 Unit | 7 | 7 | 7 | | | 2,000 | 2,000 | 2,000 | | | 1,760 | 6,000 | 7,270 | 640 | 1,660 | 2,460 | 2.9 | 7.1 | 11.3 | 3.62 | A++ | 7.48 | 281 |
| | | 7 | 7 | 9 | | | 2,000 | 2,000 | 2,500 | | | 1,760 | 6,500 | 7,900 | 640 | 1,780 | 2,660 | 2.9 | 7.6 | 12.2 | 3.65 | A++ | 7.48 | 281 |
| | | 7 | 7 | 12 | | | 2,000 | 2,000 | 3,500 | | | 2,280 | 7,500 | 8,850 | 650 | 2,080 | 2,980 | 3.0 | 8.9 | 13.6 | 3.61 | A++ | 7.52 | 349 |
| | | 7 | 7 | 18 | | | 1,930 | 1,930 | 4,830 | | | 2,310 | 8,690 | 10,270 | 660 | 2,500 | 3,450 | 3.0 | 10.7 | 15.8 | 3.48 | A++ | 7.91 | 391 |
| | | 7 | 7 | 24 | | | 1,660 | 1,660 | 5,650 | | | 2,550 | 8,970 | 10,430 | 680 | 2,560 | 3,530 | 3.1 | 10.9 | 16.2 | 3.51 | A++ | 7.65 | 411 |
| 7 | | 9 | 9 | | | 2,000 | 2,500 | 2,500 | | | 2,240 | 7,000 | 8,370 | 640 | 1,920 | 2,820 | 2.9 | 8.2 | 12.9 | 3.64 | A++ | 7.50 | 326 | |
| 7 | | 9 | 12 | | | 2,000 | 2,500 | 3,500 | | | 2,280 | 8,000 | 9,320 | 650 | 2,230 | 3,130 | 3.0 | 9.5 | 14.3 | 3.58 | A++ | 7.77 | 361 | |
| 7 | | 9 | 18 | | | 1,850 | 2,310 | 4,620 | | | 2,310 | 8,780 | 10,270 | 660 | 2,480 | 3,450 | 3.0 | 10.6 | 15.8 | 3.54 | A++ | 7.92 | 388 | |
| 7 | | 9 | 24 | | | 1,550 | 1,940 | 5,270 | | | 2,550 | 8,760 | 10,430 | 680 | 2,470 | 3,530 | 3.1 | 10.5 | 16.2 | 3.54 | A++ | 7.92 | 387 | |
| 7 | | 12 | 12 | | | 1,930 | 3,380 | 3,380 | | | 2,280 | 8,690 | 10,270 | 650 | 2,500 | 3,440 | 3.0 | 10.7 | 15.7 | 3.48 | A++ | 7.91 | 391 | |
| 7 | | 12 | 18 | | | 1,700 | 2,980 | 4,250 | | | 2,510 | 8,930 | 10,430 | 670 | 2,590 | 3,510 | 3.1 | 11.0 | 16.1 | 3.45 | A++ | 7.90 | 396 | |
| 7 | | 12 | 24 | | | 1,460 | 2,550 | 4,950 | | | 2,760 | 8,960 | 10,740 | 690 | 2,550 | 3,630 | 3.2 | 10.9 | 16.6 | 3.51 | A++ | 7.65 | 410 | |
| 7 | | 18 | 18 | | | 1,480 | 3,710 | 3,710 | | | 2,720 | 8,900 | 10,740 | 680 | 2,540 | 3,630 | 3.1 | 10.8 | 16.6 | 3.50 | A++ | 7.92 | 394 | |
| 7 | | 18 | 24 | | | 1,340 | 3,360 | 4,560 | | | 3,150 | 9,260 | 11,000 | 700 | 2,570 | 3,750 | 3.2 | 11.0 | 17.2 | 3.61 | A++ | 7.75 | 418 | |
| 7 | | 24 | 24 | | | 1,260 | 4,270 | 4,270 | | | 3,240 | 9,800 | 11,000 | 720 | 2,720 | 3,770 | 3.3 | 11.6 | 17.3 | 3.60 | A++ | 7.77 | 442 | |
| 9 | | 9 | 9 | | | 2,500 | 2,500 | 2,500 | | | 2,240 | 7,500 | 8,850 | 640 | 2,080 | 2,970 | 2.9 | 8.9 | 13.6 | 3.61 | A++ | 7.52 | 349 | |
| 9 | | 9 | 12 | | | 2,500 | 2,500 | 3,500 | | | 2,280 | 8,500 | 9,950 | 650 | 2,390 | 3,340 | 3.0 | 10.2 | 15.3 | 3.55 | A++ | 7.91 | 376 | |
| 9 | | 9 | 18 | | | 2,210 | 2,210 | 4,430 | | | 2,480 | 8,850 | 10,270 | 660 | 2,520 | 3,450 | 3.0 | 10.7 | 15.8 | 3.51 | A++ | 7.92 | 391 | |
| 9 | | 9 | 24 | | | 1,880 | 1,880 | 5,110 | | | 2,550 | 8,870 | 10,740 | 680 | 2,530 | 3,630 | 3.1 | 10.8 | 16.6 | 3.51 | A++ | 7.92 | 392 | |
| 9 | | 12 | 12 | | | 2,310 | 3,230 | 3,230 | | | 2,280 | 8,770 | 10,270 | 650 | 2,440 | 3,440 | 3.0 | 10.4 | 15.7 | 3.59 | A++ | 7.93 | 387 | |
| 9 | 12 | 18 | | | 1,980 | 2,770 | 3,950 | | | 2,510 | 8,700 | 10,430 | 670 | 2,420 | 3,510 | 3.1 | 10.3 | 16.1 | 3.59 | A++ | 7.93 | 384 | | |
| 9 | 12 | 24 | | | 1,770 | 2,480 | 4,810 | | | 2,760 | 9,060 | 10,900 | 690 | 2,570 | 3,690 | 3.2 | 11.0 | 16.9 | 3.52 | A++ | 7.66 | 414 | | |
| 9 | 18 | 18 | | | 1,800 | 3,600 | 3,600 | | | 2,720 | 9,000 | 10,900 | 680 | 2,560 | 3,680 | 3.1 | 10.9 | 16.8 | 3.52 | A++ | 7.65 | 412 | | |
| 9 | 18 | 24 | | | 1,640 | 3,270 | 4,450 | | | 3,150 | 9,360 | 11,000 | 700 | 2,590 | 3,750 | 3.2 | 11.0 | 17.2 | 3.61 | A++ | 7.75 | 423 | | |
| 9 | 24 | 24 | | | 1,520 | 4,140 | 4,140 | | | 3,240 | 9,800 | 11,000 | 720 | 2,660 | 3,770 | 3.3 | 11.3 | 17.3 | 3.68 | A++ | 7.79 | 440 | | |
| 12 | 12 | 12 | | | 2,980 | 2,980 | 2,980 | | | 2,480 | 8,940 | 10,430 | 660 | 2,410 | 3,500 | 3.0 | 10.3 | 16.0 | 3.71 | A++ | 7.98 | 392 | | |
| 12 | 12 | 18 | | | 2,600 | 2,600 | 3,710 | | | 2,680 | 8,910 | 10,740 | 670 | 2,410 | 3,620 | 3.1 | 10.3 | 16.6 | 3.69 | A++ | 7.97 | 391 | | |
| 12 | 12 | 24 | | | 2,350 | 2,350 | 4,560 | | | 3,110 | 9,260 | 11,000 | 690 | 2,540 | 3,740 | 3.2 | 10.8 | 17.1 | 3.64 | A++ | 7.75 | 418 | | |
| 12 | 18 | 18 | | | 2,390 | 3,410 | 3,410 | | | 3,110 | 9,210 | 11,000 | 690 | 2,530 | 3,740 | 3.2 | 10.8 | 17.1 | 3.64 | A++ | 7.75 | 416 | | |
| 12 | 18 | 24 | | | 2,240 | 3,200 | 4,360 | | | 3,200 | 9,800 | 11,000 | 710 | 2,750 | 3,760 | 3.2 | 11.7 | 17.2 | 3.57 | A++ | 7.75 | 442 | | |
| 12 | 24 | 24 | | | 2,000 | 3,900 | 3,900 | | | 3,290 | 9,800 | 11,000 | 730 | 2,750 | 3,780 | 3.3 | 11.7 | 17.3 | 3.57 | A++ | 7.75 | 442 | | |
| 18 | 18 | 18 | | | 3,260 | 3,270 | 3,270 | | | 3,150 | 9,800 | 11,000 | 700 | 2,750 | 3,750 | 3.2 | 11.7 | 17.2 | 3.57 | A++ | 7.75 | 442 | | |
| 18 | 18 | 24 | | | 2,920 | 2,920 | 3,960 | | | 3,240 | 9,800 | 11,000 | 720 | 2,750 | 3,770 | 3.3 | 11.7 | 17.3 | 3.57 | A++ | 7.75 | 442 | | |

| Outdoor Unit | A | B | C | D | E | Cooling Capacity | | | | | Capacity | | | Power Consumption | | | Current | | | Effic. NOM. Cooling at 35°C/27°C EER | Seasonal Efficiency (According to EN14825) Class | SEER | Qce kWh | | | | | | |
|--------------|--------|---|---|---|----|------------------|---|---|---|---|----------|-------|-------|-------------------|-----|-----|---------|-------|--------|---|---|-------|------------|------|------|------|-----|------|-----|
| | | | | | | W | | | | | W | | | W | | | A | | | | | | | | | | | | |
| | | | | | | A | B | C | D | E | MIN | STD | MAX | MIN | STD | MAX | MIN | STD | MAX | | | | | MIN | STD | MAX | | | |
| AJ100TXJ5KG | 4 Unit | 7 | 7 | 7 | 7 | | | | | | 2,000 | 2,000 | 2,000 | 2,000 | | | 2,350 | 8,000 | 9,320 | 670 | 2,170 | 3,160 | 3.1 | 9.2 | 14.5 | 3.68 | A++ | 7.79 | 359 |
| | | 7 | 7 | 7 | 9 | | | | | | 2,000 | 2,000 | 2,000 | 2,500 | | | 2,350 | 8,500 | 9,950 | 670 | 2,290 | 3,360 | 3.1 | 9.8 | 15.4 | 3.71 | A++ | 7.95 | 374 |
| | | 7 | 7 | 7 | 12 | | | | | | 1,850 | 1,850 | 1,850 | 3,230 | | | 2,380 | 8,780 | 10,270 | 680 | 2,390 | 3,470 | 3.1 | 10.2 | 15.9 | 3.68 | A++ | 7.96 | 386 |
| | | 7 | 7 | 7 | 18 | | | | | | 1,580 | 1,580 | 1,580 | 3,950 | | | 2,590 | 8,690 | 10,430 | 690 | 2,330 | 3,540 | 3.2 | 9.9 | 16.2 | 3.73 | A++ | 7.97 | 382 |
| | | 7 | 7 | 7 | 24 | | | | | | 1,420 | 1,420 | 1,420 | 4,820 | | | 2,840 | 9,080 | 10,900 | 710 | 2,460 | 3,710 | 3.2 | 10.5 | 17.0 | 3.69 | A++ | 7.71 | 412 |
| | | 7 | 7 | 9 | 9 | | | | | | 1,930 | 1,930 | 2,420 | 2 | | | | | | | | | | | | | | | |

Combination guide

4-6. AJ100TXJ5KG/EU

| Outdoor Unit | A | B | C | D | E | Cooling Capacity | | | | | Capacity | | | Power Consumption | | | Current | | | Effic. NOM. Cooling at 35 °C/27 °C | Seasonal Efficiency (According to EN14825) Class | SEER | Qce kWh | |
|--------------|---|---|----|----|----|------------------|-------|-------|-------|-------|----------|-------|--------|-------------------|-----|-------|---------|-----|------|------------------------------------|--|------|---------|-----|
| | | | | | | W | | | | | W | | | W | | | A | | | | | | | |
| | | | | | | A | B | C | D | E | MIN | STD | MAX | MIN | STD | MAX | MIN | STD | MAX | | | | | MIN |
| AJ100TXJ5KG | 5 | 7 | 7 | 7 | 7 | 7 | 1,900 | 1,900 | 1,900 | 1,900 | 1,900 | 2,630 | 9,500 | 10,270 | 700 | 2,570 | 3,490 | 3.2 | 11.5 | 16.0 | 3.69 | A++ | 7.78 | 427 |
| | | 7 | 7 | 7 | 7 | 9 | 1,820 | 1,820 | 1,820 | 1,820 | 2,270 | 2,630 | 9,550 | 10,430 | 700 | 2,600 | 3,550 | 3.2 | 11.6 | 16.2 | 3.68 | A++ | 7.78 | 430 |
| | | 7 | 7 | 7 | 7 | 12 | 1,680 | 1,680 | 1,680 | 1,680 | 2,940 | 2,660 | 9,660 | 10,740 | 710 | 2,630 | 3,650 | 3.2 | 11.7 | 16.7 | 3.68 | A++ | 7.78 | 434 |
| | | 7 | 7 | 7 | 7 | 18 | 1,540 | 1,540 | 1,540 | 1,540 | 3,840 | 3,240 | 10,000 | 10,900 | 720 | 2,750 | 3,720 | 3.3 | 12.2 | 17.0 | 3.64 | A++ | 7.79 | 449 |
| | | 7 | 7 | 7 | 7 | 24 | 1,350 | 1,350 | 1,350 | 1,350 | 4,600 | 3,330 | 10,000 | 11,000 | 740 | 2,750 | 3,790 | 3.4 | 12.2 | 17.3 | 3.64 | A++ | 7.79 | 449 |
| | | 7 | 7 | 7 | 9 | 9 | 1,750 | 1,750 | 1,750 | 2,180 | 2,180 | 2,630 | 9,610 | 10,430 | 700 | 2,610 | 3,550 | 3.2 | 11.6 | 16.2 | 3.68 | A++ | 7.78 | 432 |
| | | 7 | 7 | 7 | 9 | 12 | 1,620 | 1,620 | 1,620 | 2,020 | 2,830 | 2,840 | 9,710 | 10,740 | 710 | 2,670 | 3,650 | 3.2 | 11.9 | 16.7 | 3.64 | A++ | 7.77 | 437 |
| | | 7 | 7 | 7 | 9 | 18 | 1,480 | 1,480 | 1,480 | 1,860 | 3,700 | 3,240 | 10,000 | 11,000 | 720 | 2,730 | 3,770 | 3.3 | 12.1 | 17.3 | 3.66 | A++ | 7.79 | 449 |
| | | 7 | 7 | 7 | 9 | 24 | 1,310 | 1,310 | 1,310 | 1,630 | 4,440 | 3,330 | 10,000 | 11,000 | 740 | 2,730 | 3,790 | 3.4 | 12.1 | 17.3 | 3.66 | A++ | 7.79 | 449 |
| | | 7 | 7 | 7 | 12 | 12 | 1,540 | 1,540 | 1,540 | 2,690 | 2,690 | 3,200 | 10,000 | 10,900 | 710 | 2,750 | 3,710 | 3.2 | 12.2 | 17.0 | 3.64 | A++ | 7.79 | 449 |
| | | 7 | 7 | 7 | 12 | 18 | 1,380 | 1,380 | 1,380 | 2,410 | 3,450 | 3,290 | 10,000 | 11,000 | 730 | 2,760 | 3,780 | 3.3 | 12.3 | 17.3 | 3.62 | A++ | 7.78 | 450 |
| | | 7 | 7 | 7 | 12 | 24 | 1,230 | 1,230 | 1,230 | 2,150 | 4,160 | 3,380 | 10,000 | 11,000 | 750 | 2,760 | 3,800 | 3.4 | 12.3 | 17.4 | 3.62 | A++ | 7.78 | 450 |
| | | 7 | 7 | 7 | 18 | 18 | 1,240 | 1,240 | 1,240 | 3,140 | 3,140 | 3,330 | 10,000 | 11,000 | 740 | 2,760 | 3,790 | 3.4 | 12.3 | 17.3 | 3.62 | A++ | 7.78 | 450 |
| | | 7 | 7 | 9 | 9 | 9 | 1,680 | 1,680 | 2,100 | 2,100 | 2,100 | 2,630 | 9,660 | 10,740 | 700 | 2,630 | 3,650 | 3.2 | 11.7 | 16.7 | 3.68 | A++ | 7.78 | 434 |
| | | 7 | 7 | 9 | 9 | 12 | 1,600 | 1,600 | 2,000 | 2,000 | 2,800 | 2,840 | 9,710 | 10,900 | 710 | 2,670 | 3,710 | 3.2 | 12.2 | 17.0 | 3.64 | A++ | 7.79 | 449 |
| | | 7 | 7 | 9 | 9 | 18 | 1,430 | 1,430 | 1,790 | 1,790 | 3,560 | 3,240 | 10,000 | 11,000 | 720 | 2,760 | 3,770 | 3.3 | 12.3 | 17.3 | 3.62 | A++ | 7.78 | 450 |
| | | 7 | 7 | 9 | 9 | 24 | 1,270 | 1,270 | 1,580 | 1,580 | 4,300 | 3,330 | 10,000 | 11,000 | 740 | 2,760 | 3,790 | 3.4 | 12.3 | 17.3 | 3.62 | A++ | 7.78 | 450 |
| | | 7 | 7 | 9 | 12 | 12 | 1,480 | 1,480 | 1,860 | 2,590 | 2,590 | 3,200 | 10,000 | 11,000 | 710 | 2,750 | 3,760 | 3.2 | 12.2 | 17.2 | 3.64 | A++ | 7.79 | 449 |
| | | 7 | 7 | 9 | 12 | 18 | 1,330 | 1,330 | 1,680 | 2,330 | 3,330 | 3,290 | 10,000 | 11,000 | 730 | 2,780 | 3,780 | 3.3 | 12.3 | 17.3 | 3.60 | A++ | 7.78 | 450 |
| | | 7 | 7 | 9 | 12 | 24 | 1,190 | 1,190 | 1,490 | 2,080 | 4,050 | 3,380 | 10,000 | 11,000 | 750 | 2,780 | 3,800 | 3.4 | 12.3 | 17.4 | 3.60 | A++ | 7.78 | 450 |
| | | 7 | 7 | 9 | 18 | 18 | 1,210 | 1,210 | 1,520 | 3,030 | 3,030 | 3,330 | 10,000 | 11,000 | 740 | 2,780 | 3,790 | 3.4 | 12.3 | 17.3 | 3.60 | A++ | 7.78 | 450 |
| | | 7 | 7 | 12 | 12 | 12 | 1,370 | 1,370 | 2,420 | 2,420 | 2,420 | 3,240 | 10,000 | 11,000 | 720 | 2,750 | 3,770 | 3.3 | 12.2 | 17.3 | 3.64 | A++ | 7.79 | 449 |
| | | 7 | 7 | 12 | 12 | 18 | 1,250 | 1,250 | 2,190 | 2,190 | 3,120 | 3,290 | 10,000 | 11,000 | 730 | 2,760 | 3,780 | 3.3 | 12.3 | 17.3 | 3.62 | A++ | 7.78 | 450 |
| | | 7 | 9 | 9 | 9 | 9 | 1,620 | 2,020 | 2,020 | 2,020 | 2,020 | 2,800 | 9,700 | 10,740 | 700 | 2,610 | 3,650 | 3.2 | 11.6 | 16.7 | 3.71 | A++ | 7.79 | 436 |
| | | 7 | 9 | 9 | 9 | 12 | 1,550 | 1,920 | 1,920 | 1,920 | 2,690 | 3,200 | 10,000 | 10,900 | 710 | 2,750 | 3,710 | 3.2 | 12.2 | 17.0 | 3.64 | A++ | 7.79 | 449 |
| | | 7 | 9 | 9 | 9 | 18 | 1,390 | 1,720 | 1,720 | 1,720 | 3,450 | 3,240 | 10,000 | 11,000 | 720 | 2,760 | 3,770 | 3.3 | 12.3 | 17.3 | 3.62 | A++ | 7.78 | 450 |
| | | 7 | 9 | 9 | 9 | 24 | 1,240 | 1,530 | 1,530 | 1,530 | 4,170 | 3,330 | 10,000 | 11,000 | 740 | 2,760 | 3,790 | 3.4 | 12.3 | 17.3 | 3.62 | A++ | 7.78 | 450 |
| | | 7 | 9 | 9 | 12 | 12 | 1,440 | 1,790 | 1,790 | 2,490 | 2,490 | 3,200 | 10,000 | 11,000 | 710 | 2,720 | 3,760 | 3.2 | 12.1 | 17.2 | 3.68 | A++ | 7.78 | 434 |
| | | 7 | 9 | 9 | 12 | 18 | 1,290 | 1,610 | 1,610 | 2,260 | 3,230 | 3,290 | 10,000 | 11,000 | 730 | 2,760 | 3,780 | 3.3 | 12.3 | 17.3 | 3.62 | A++ | 7.78 | 450 |
| | | 7 | 9 | 9 | 12 | 24 | 1,160 | 1,450 | 1,450 | 2,020 | 3,920 | 3,380 | 10,000 | 11,000 | 750 | 2,760 | 3,800 | 3.4 | 12.3 | 17.4 | 3.62 | A++ | 7.78 | 450 |
| | | 7 | 9 | 9 | 18 | 18 | 1,180 | 1,470 | 1,470 | 2,940 | 2,940 | 3,330 | 10,000 | 11,000 | 740 | 2,780 | 3,790 | 3.4 | 12.3 | 17.3 | 3.60 | A++ | 7.78 | 450 |
| | | 7 | 9 | 12 | 12 | 12 | 1,340 | 1,670 | 2,330 | 2,330 | 2,330 | 3,240 | 10,000 | 11,000 | 720 | 2,750 | 3,770 | 3.3 | 12.2 | 17.3 | 3.64 | A++ | 7.79 | 449 |
| | | 7 | 9 | 12 | 12 | 18 | 1,210 | 1,520 | 2,120 | 2,120 | 3,030 | 3,290 | 10,000 | 11,000 | 730 | 2,750 | 3,780 | 3.3 | 12.2 | 17.3 | 3.64 | A++ | 7.79 | 449 |
| | | 7 | 12 | 12 | 12 | 12 | 1,240 | 2,190 | 2,190 | 2,190 | 2,190 | 3,240 | 10,000 | 11,000 | 720 | 2,750 | 3,770 | 3.3 | 12.2 | 17.3 | 3.64 | A++ | 7.79 | 449 |
| | | 9 | 9 | 9 | 9 | 9 | 2,000 | 2,000 | 2,000 | 2,000 | 2,000 | 3,000 | 10,000 | 11,000 | 700 | 2,750 | 3,700 | 3.2 | 12.2 | 16.9 | 3.64 | A++ | 7.79 | 449 |
| | | 9 | 9 | 9 | 9 | 12 | 1,850 | 1,850 | 1,850 | 1,850 | 2,600 | 3,200 | 10,000 | 11,000 | 710 | 2,750 | 3,760 | 3.2 | 12.2 | 17.2 | 3.64 | A++ | 7.79 | 449 |
| | | 9 | 9 | 9 | 9 | 18 | 1,670 | 1,670 | 1,670 | 1,670 | 3,320 | 3,240 | 10,000 | 11,000 | 720 | 2,760 | 3,770 | 3.3 | 12.3 | 17.3 | 3.62 | A++ | 7.78 | 450 |
| | | 9 | 9 | 9 | 9 | 24 | 1,490 | 1,490 | 1,490 | 1,490 | 4,040 | 3,330 | 10,000 | 11,000 | 740 | 2,760 | 3,790 | 3.4 | 12.3 | 17.3 | 3.62 | A++ | 7.78 | 450 |
| | | 9 | 9 | 9 | 12 | 12 | 1,720 | 1,720 | 1,720 | 2,420 | 2,420 | 3,200 | 10,000 | 11,000 | 710 | 2,750 | 3,760 | 3.2 | 12.2 | 17.2 | 3.64 | A++ | 7.79 | 449 |
| | | 9 | 9 | 9 | 12 | 18 | 1,560 | 1,560 | 1,560 | 2,190 | 3,130 | 3,290 | 10,000 | 11,000 | 730 | 2,760 | 3,780 | 3.3 | 12.3 | 17.3 | 3.62 | A++ | 7.78 | 450 |
| | | 9 | 9 | 12 | 12 | 12 | 1,610 | 1,610 | 2,260 | 2,260 | 2,260 | 3,240 | 10,000 | 11,000 | 720 | 2,750 | 3,770 | 3.3 | 12.2 | 17.3 | 3.64 | A++ | 7.79 | 449 |
| | | 9 | 9 | 12 | 12 | 18 | 1,470 | 1,470 | 2,060 | 2,060 | 2,940 | 3,290 | 10,000 | 11,000 | 730 | 2,760 | 3,780 | 3.3 | 12.3 | 17.3 | 3.62 | A++ | 7.78 | 450 |
| | | 9 | 12 | 12 | 12 | 12 | 1,520 | 2,120 | 2,120 | 2,120 | 2,120 | 3,240 | 10,000 | 11,000 | 720 | 2,750 | 3,770 | 3.3 | 12.2 | 17.3 | 3.64 | A++ | 7.79 | 449 |

Heating

| Outdoor Unit | A | B | C | D | E | Heating Capacity | | | | | Capacity | | | Power Consumption | | | Current | | | Effic. NOM. Heating at 7 °C/ 20 °C COP ¹ | Seasonal Efficiency (According to EN14825) Class | SCOP | P design kW | Qhe kWh |
|--------------|---|----|----|---|---|------------------|-------|-------|---|---|----------|--------|--------|-------------------|-------|-------|---------|------|------|---|--|------|-------------|---------|
| | | | | | | W | | | | | W | | | W | | | A | | | | | | | |
| | | | | | | A | B | C | D | E | MIN | STD | MAX | MIN | STD | MAX | MIN | STD | MAX | | | | | |
| AJ100TXJ5KG | 2 | 7 | 7 | | | | 2,200 | 2,200 | | | 1,240 | 4,400 | 5,530 | 460 | 1,070 | 1,520 | 2.1 | 4.6 | 7.0 | 4.10 | A+ | 4.16 | 3.05 | 1,028 |
| | | 7 | 9 | | | | 2,200 | 3,300 | | | 1,240 | 5,500 | 6,790 | 460 | 1,360 | 1,850 | 2.1 | 5.8 | 8.5 | 4.05 | A+ | 4.15 | 4.21 | 1,418 |
| | | 7 | 12 | | | | 2,200 | 4,000 | | | 1,270 | 6,200 | 7,580 | 470 | 1,490 | 2,060 | 2.2 | 6.3 | 9.4 | 4.15 | A+ | 4.19 | 4.91 | 1,638 |
| | | 7 | 18 | | | | 2,200 | 6,000 | | | 1,300 | 8,200 | 10,110 | 480 | 2,010 | 2,750 | 2.2 | 8.6 | 12.6 | 4.08 | A+ | 4.09 | 5.88 | 2,010 |
| | | 7 | 24 | | | | 2,200 | 7,800 | | | 1,500 | 10,000 | 12,480 | 500 | 2,490 | 3,390 | 2.3 | 10.6 | 15.5 | 4.01 | A+ | 4.03 | 7.70 | 2,671 |
| | | 9 | 9 | | | | 3,300 | 3,300 | | | 1,240 | 6,600 | 8,220 | 460 | 1,630 | 2,230 | 2.1 | 6.9 | 10.2 | 4.06 | A+ | 4.19 | 4.91 | 1,638 |
| | | 9 | 12 | | | | 3,300 | 4,000 | | | 1,270 | 7,300 | 9,010 | 470 | 1,810 | 2,440 | 2.2 | 7.7 | 11.2 | 4.04 | A+ | 4.19 | 4.91 | 1,638 |
| | | 9 | 18 | | | | 3,300 | 6,000 | | | 1,300 | 9,300 | 11,690 | 480 | 2,320 | 3,160 | 2.2 | 9.9 | 14.5 | 4.01 | A+ | 4.03 | 7.70 | 2,671 |
| | | 9 | 24 | | | | 3,350 | 7,450 | | | 1,500 | 10,600 | 13,110 | 500 | 2,640 | 3,560 | 2.3 | 11.2 | 16.3 | 4.02 | A+ | 4.03 | 7.70 | 2,671 |
| | | 12 | 12 | | | | 4,000 | 4,000 | | | 1,270 | 8,000 | 9,800 | 470 | 1,940 | 2,650 | 2.2 | 8.3 | 12.1 | 4.13 | A+ | 4.19 | 4.91 | 1,638 |
| | | 12 | 18 | | | | 4,000 | 6,000 | | | 1,470 | 10,000 | 12,320 | 490 | 2,490 | 3,330 | 2.2 | 10.6 | 15.2 | 4.01 | A+ | 4.03 | 7.70 | 2,671 |
| | | 12 | 24 | | | | 3,590 | 7,010 | | | 1,530 | 10,600 | 13,110 | 510 | 2,670 | 3,560 | 2.3 | 11.4 | 16.3 | | | | | |

Combination guide

| Outdoor Unit | A | B | C | D | E | Heating Capacity | | | | | Capacity | | | Power Consumption | | | Current | | | Effic. NOM. Heating at 7 °C/ 20 °C COP ¹ | Seasonal Efficiency (According to EN14825) Class | SCOP | P design kW | Qhe kWh |
|--------------|----|------|----|-------|-------|------------------|-------|-------|--------|--------|----------|--------|--------|-------------------|-------|-------|---------|------|------|---|--|------|-------------|---------|
| | | | | | | W | | | | | W | | | W | | | A | | | | | | | |
| | | | | | | A | B | C | D | E | MIN | STD | MAX | MIN | STD | MAX | MIN | STD | MAX | | | | | |
| AJ100TXJ5KG | 4 | Unit | 7 | 7 | 7 | 7 | 2,200 | 2,200 | 2,200 | 2,200 | 1,400 | 8,800 | 9,800 | 520 | 2,110 | 2,700 | 2.4 | 9.0 | 12.4 | 4.18 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 7 | 7 | 9 | 2,140 | 2,140 | 2,140 | 3,210 | 1,560 | 9,630 | 11,380 | 520 | 2,320 | 3,120 | 2.4 | 9.9 | 14.3 | 4.15 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 7 | 7 | 12 | 2,010 | 2,010 | 2,010 | 3,660 | 1,590 | 9,690 | 12,170 | 530 | 2,330 | 3,330 | 2.4 | 9.9 | 15.2 | 4.15 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 7 | 7 | 18 | 1,730 | 1,730 | 1,730 | 4,710 | 1,780 | 9,900 | 12,170 | 540 | 2,410 | 3,350 | 2.5 | 10.3 | 15.3 | 4.11 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 7 | 7 | 24 | 1,630 | 1,630 | 1,630 | 5,770 | 1,960 | 10,660 | 12,320 | 560 | 2,620 | 3,410 | 2.6 | 11.2 | 15.6 | 4.07 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 7 | 9 | 9 | 1,950 | 1,950 | 2,920 | 2,920 | 1,560 | 9,740 | 11,530 | 520 | 2,350 | 3,160 | 2.4 | 10.0 | 14.5 | 4.15 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 7 | 9 | 12 | 1,840 | 1,840 | 2,760 | 3,350 | 1,590 | 9,790 | 11,850 | 530 | 2,390 | 3,250 | 2.4 | 10.2 | 14.9 | 4.09 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 7 | 9 | 18 | 1,610 | 1,610 | 2,410 | 4,380 | 1,890 | 10,010 | 12,170 | 540 | 2,440 | 3,350 | 2.5 | 10.4 | 15.3 | 4.11 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 7 | 9 | 24 | 1,530 | 1,530 | 2,290 | 5,410 | 1,960 | 10,760 | 12,480 | 560 | 2,620 | 3,450 | 2.6 | 11.2 | 15.8 | 4.10 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 7 | 12 | 12 | 1,750 | 1,750 | 3,190 | 3,190 | 1,750 | 9,880 | 12,170 | 530 | 2,360 | 3,340 | 2.4 | 10.1 | 15.3 | 4.19 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 7 | 12 | 18 | 1,630 | 1,630 | 2,960 | 4,440 | 1,930 | 10,660 | 12,320 | 550 | 2,610 | 3,390 | 2.5 | 11.1 | 15.5 | 4.09 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 7 | 12 | 24 | 1,470 | 1,470 | 2,670 | 5,210 | 2,280 | 10,820 | 12,800 | 570 | 2,630 | 3,540 | 2.6 | 11.2 | 16.2 | 4.11 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 7 | 18 | 18 | 1,460 | 1,460 | 3,970 | 3,970 | 2,240 | 10,860 | 12,800 | 560 | 2,640 | 3,530 | 2.6 | 11.2 | 16.2 | 4.11 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 7 | 18 | 24 | 1,330 | 1,330 | 3,630 | 4,710 | 2,320 | 11,000 | 12,960 | 580 | 2,680 | 3,600 | 2.7 | 11.4 | 16.5 | 4.10 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 9 | 9 | 9 | 1,790 | 2,690 | 2,690 | 2,690 | 1,720 | 9,860 | 12,170 | 530 | 2,390 | 3,330 | 2.4 | 10.2 | 15.2 | 4.13 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 9 | 9 | 12 | 1,710 | 2,560 | 2,560 | 3,100 | 1,750 | 9,930 | 12,320 | 530 | 2,410 | 3,370 | 2.4 | 10.3 | 15.4 | 4.12 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 9 | 9 | 18 | 1,590 | 2,380 | 2,380 | 4,330 | 1,890 | 10,680 | 12,480 | 540 | 2,620 | 3,430 | 2.5 | 11.2 | 15.7 | 4.08 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 9 | 9 | 24 | 1,440 | 2,160 | 2,160 | 5,100 | 2,240 | 10,860 | 12,960 | 560 | 2,670 | 3,580 | 2.6 | 11.4 | 16.4 | 4.07 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 9 | 12 | 12 | 1,630 | 2,440 | 2,960 | 2,960 | 1,860 | 9,990 | 12,170 | 530 | 2,440 | 3,340 | 2.4 | 10.4 | 15.3 | 4.10 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 9 | 12 | 18 | 1,530 | 2,290 | 2,780 | 4,170 | 1,930 | 10,770 | 12,480 | 550 | 2,640 | 3,440 | 2.5 | 11.2 | 15.7 | 4.08 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 9 | 12 | 24 | 1,400 | 2,100 | 2,540 | 4,960 | 2,280 | 11,000 | 12,960 | 570 | 2,680 | 3,580 | 2.6 | 11.4 | 16.4 | 4.11 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 9 | 18 | 18 | 1,390 | 2,070 | 3,770 | 3,770 | 2,240 | 11,000 | 12,960 | 560 | 2,680 | 3,580 | 2.6 | 11.4 | 16.4 | 4.11 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 9 | 18 | 24 | 1,250 | 1,880 | 3,420 | 4,450 | 2,320 | 11,000 | 13,110 | 580 | 2,680 | 3,640 | 2.7 | 11.4 | 16.7 | 4.11 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 12 | 12 | 12 | 1,560 | 2,830 | 2,830 | 2,830 | 1,890 | 10,050 | 12,320 | 540 | 2,420 | 3,380 | 2.5 | 10.3 | 15.5 | 4.15 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 12 | 12 | 18 | 1,470 | 2,670 | 2,670 | 4,010 | 2,200 | 10,820 | 12,800 | 550 | 2,650 | 3,520 | 2.5 | 11.3 | 16.1 | 4.08 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 12 | 12 | 24 | 1,350 | 2,440 | 2,440 | 4,770 | 2,280 | 11,000 | 12,960 | 570 | 2,680 | 3,590 | 2.6 | 11.4 | 16.4 | 4.11 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 12 | 18 | 18 | 1,330 | 2,410 | 3,630 | 3,630 | 2,280 | 11,000 | 12,960 | 570 | 2,680 | 3,580 | 2.6 | 11.4 | 16.4 | 4.11 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 12 | 18 | 24 | 1,210 | 2,200 | 3,300 | 4,290 | 2,360 | 11,000 | 13,430 | 590 | 2,680 | 3,730 | 2.7 | 11.4 | 17.1 | 4.11 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 18 | 18 | 18 | 1,190 | 3,270 | 3,270 | 3,270 | 2,320 | 11,000 | 13,430 | 580 | 2,680 | 3,720 | 2.7 | 11.4 | 17.0 | 4.11 | A+ | 4.25 | 791 | 2,607 |
| | | | 9 | 9 | 9 | 9 | 2,490 | 2,490 | 2,490 | 2,490 | 1,820 | 9,960 | 12,480 | 520 | 2,310 | 3,410 | 2.4 | 9.8 | 15.6 | 4.32 | A+ | 4.32 | 791 | 2,564 |
| | | | 9 | 9 | 9 | 12 | 2,380 | 2,380 | 2,380 | 2,880 | 1,860 | 10,020 | 12,320 | 530 | 2,340 | 3,370 | 2.4 | 10.0 | 15.4 | 4.28 | A+ | 4.25 | 791 | 2,607 |
| | | | 9 | 9 | 9 | 18 | 2,240 | 2,240 | 2,240 | 4,080 | 2,160 | 10,800 | 12,800 | 540 | 2,610 | 3,510 | 2.5 | 11.1 | 16.1 | 4.14 | A+ | 4.25 | 791 | 2,607 |
| | | | 9 | 9 | 9 | 24 | 2,050 | 2,050 | 2,050 | 4,850 | 2,240 | 11,000 | 12,960 | 560 | 2,680 | 3,580 | 2.6 | 11.4 | 16.4 | 4.11 | A+ | 4.25 | 791 | 2,607 |
| | | | 9 | 9 | 12 | 12 | 2,410 | 2,410 | 2,920 | 2,920 | 1,860 | 10,660 | 12,480 | 530 | 2,510 | 3,420 | 2.4 | 10.7 | 15.7 | 4.24 | A+ | 4.25 | 791 | 2,607 |
| | | | 9 | 9 | 12 | 18 | 2,160 | 2,160 | 2,620 | 3,930 | 2,200 | 10,870 | 12,960 | 550 | 2,630 | 3,560 | 2.5 | 11.2 | 16.3 | 4.13 | A+ | 4.25 | 791 | 2,607 |
| | | | 9 | 9 | 12 | 24 | 1,970 | 1,970 | 2,400 | 4,660 | 2,280 | 11,000 | 13,110 | 570 | 2,680 | 3,620 | 2.6 | 11.4 | 16.6 | 4.11 | A+ | 4.25 | 791 | 2,607 |
| 9 | 9 | 18 | 18 | 1,950 | 1,950 | 3,550 | 3,550 | 2,240 | 11,000 | 13,110 | 560 | 2,680 | 3,620 | 2.6 | 11.4 | 16.6 | 4.11 | A+ | 4.25 | 791 | 2,607 | | | |
| 9 | 9 | 18 | 24 | 1,780 | 1,780 | 3,240 | 4,200 | 2,320 | 11,000 | 13,590 | 580 | 2,680 | 3,760 | 2.7 | 11.4 | 17.2 | 4.11 | A+ | 4.25 | 791 | 2,607 | | | |
| 9 | 12 | 12 | 12 | 2,320 | 2,810 | 2,810 | 2,810 | 1,890 | 10,750 | 12,480 | 540 | 2,600 | 3,430 | 2.5 | 11.1 | 15.7 | 4.13 | A+ | 4.25 | 791 | 2,607 | | | |
| 9 | 12 | 12 | 18 | 2,100 | 2,540 | 2,540 | 3,820 | 2,200 | 11,000 | 12,960 | 550 | 2,680 | 3,570 | 2.5 | 11.4 | 16.3 | 4.11 | A+ | 4.25 | 791 | 2,607 | | | |
| 9 | 12 | 12 | 24 | 1,910 | 2,300 | 2,300 | 4,490 | 2,280 | 11,000 | 13,110 | 570 | 2,680 | 3,630 | 2.6 | 11.4 | 16.6 | 4.11 | A+ | 4.25 | 791 | 2,607 | | | |
| 9 | 12 | 18 | 18 | 1,880 | 2,280 | 3,420 | 3,420 | 2,280 | 11,000 | 13,110 | 570 | 2,680 | 3,620 | 2.6 | 11.4 | 16.6 | 4.11 | A+ | 4.25 | 791 | 2,607 | | | |
| 12 | 12 | 12 | 12 | 2,700 | 2,700 | 2,700 | 2,700 | 2,160 | 10,800 | 12,800 | 540 | 2,610 | 3,510 | 2.5 | 11.1 | 16.1 | 4.14 | A+ | 4.25 | 791 | 2,607 | | | |
| 12 | 12 | 12 | 18 | 2,440 | 2,440 | 2,440 | 3,680 | 2,240 | 11,000 | 12,960 | 560 | 2,680 | 3,570 | 2.6 | 11.4 | 16.3 | 4.11 | A+ | 4.25 | 791 | 2,607 | | | |
| 12 | 12 | 12 | 24 | 2,220 | 2,220 | 2,220 | 4,340 | 2,320 | 11,000 | 13,430 | 580 | 2,680 | 3,720 | 2.7 | 11.4 | 17.0 | 4.11 | A+ | 4.25 | 791 | 2,607 | | | |
| 12 | 12 | 18 | 18 | 2,200 | 2,200 | 3,300 | 3,300 | 2,280 | 11,000 | 13,430 | 570 | 2,680 | 3,710 | 2.6 | 11.4 | 17.0 | 4.11 | A+ | 4.25 | 791 | 2,607 | | | |

| Outdoor Unit | A | B | C | D | E | Heating Capacity | | | | | Capacity | | | Power Consumption | | | Current | | | Effic. NOM. Heating at 7 °C/ 20 °C COP ¹ | Seasonal Efficiency (According to EN14825) Class | SCOP | P design kW | Qhe kWh | | |
|--------------|---|------|---|---|---|------------------|----|-------|-------|-------|----------|-------|--------|-------------------|--------|-------|---------|-------|------|---|--|------|-------------|---------|-------|-------|
| | | | | | | W | | | | | W | | | W | | | A | | | | | | | | | |
| | | | | | | A | B | C | D | E | MIN | STD | MAX | MIN | STD | MAX | MIN | STD | MAX | | | | | | MIN | STD |
| AJ100TXJ5KG | 5 | Unit | 7 | 7 | 7 | 7 | 7 | 2,200 | 2,200 | 2,200 | 2,200 | 2,200 | 1,650 | 11,000 | 13,110 | 550 | 2,560 | 3,610 | 2.5 | 11.7 | 16.5 | 4.30 | A+ | 4.25 | 791 | 2,607 |
| | | | 7 | 7 | 7 | 7 | 9 | 2,080 | 2,080 | 2,080 | 3,120 | 1,820 | 11,440 | 12,960 | 550 | 2,670 | 3,570 | 2.5 | 12.2 | 16.3 | 4.28 | A+ | 4.25 | 791 | 2,607 | |
| | | | 7 | 7 | 7 | 7 | 12 | 1,990 | 1,990 | 1,990 | 3,620 | 1,850 | 11,580 | 13,110 | 560 | 2,720 | 3,610 | 2.6 | 12.4 | 16.5 | 4.26 | A+ | 4.25 | 791 | 2,607 | |
| | | | 7 | 7 | 7 | 7 | 18 | 1,710 | 1,710 | 1,710 | 4,660 | 2,000 | 11,500 | 13,430 | 570 | 2,700 | 3,710 | 2.6 | 12.3 | 17.0 | 4.26 | A+ | 4.25 | 791 | 2,607 | |
| | | | 7 | 7 | 7 | 7 | 24 | 1,580 | 1,580 | 1,580 | 5,610 | 2,360 | 11,930 | 13,750 | 590 | 2,810 | 3,810 | 2.7 | 12.8 | 17.4 | 4.24 | A+ | 4.25 | 791 | 2,607 | |
| | | | 7 | 7 | 7 | 9 | 9 | 1,950 | 1,950 | 2,930 | 2,930 | 1,930 | 11,710 | 13,430 | 550 | 2,750 | 3,690 | 2.5 | 12.5 | 16.9 | 4.26 | A+ | 4.25 | 791 | 2,607 | |
| | | | 7 | 7 | 7 | 9 | 12 | 1,880 | 1,880 | 2,820 | 3,420 | 1,960 | 11,880 | 13,110 | 560 | 2,800 | 3,610 | 2.6 | 12.3 | 16.5 | 4.24 | A+ | 4.25 | 791 | 2,607 | |
| | | | 7 | 7 | 7 | 9 | 18 | 1,630 | 1,630 | 2,440 | 4,450 | 2,280 | 11,780 | 13,590 | 570 | 2,790 | 3,750 | 2.6 | 12.7 | 17.2 | 4.22 | A+ | 4.25 | 791 | 2,607 | |
| | | | 7 | 7 | 7 | 9 | 24 | 1,490 | 1,490 | 2,240 | 5,290 | 2,360 | 12,000 | 13,900 | 590 | 2,820 | 3,860 | 2.7 | 12.8 | 17.7 | 4.26 | A+ | 4.25 | 791 | 2,607 | |
| | | | 7 | 7 | 7 | 12 | 12 | 1,730 | 1,730 | 3,140 | 3,140 | 1,960 | 11,470 | 13,430 | 560 | 2,680 | 3,700 | 2.6 | 12.2 | 16.9 | 4.28 | A+ | 4.25 | 791 | 2,607 | |
| | | | 7 | 7 | 7 | 12 | 18 | 1,490 | 1, | | | | | | | | | | | | | | | | | |